

**Solution Guide to 2MP License  
Plate  
Recognition Bullet Camera  
V1.0.0**

## **Content**

|  |   |
|--|---|
| Purpose of this Document.....                              | 4 |
| Product Introduction.....                                  | 4 |
| Site Survey.....   | 4 |
| Site Survey Concerns.....                                  | 4 |
| Engineering Scheme.....                                    | 5 |
| Sketch of Installation Angle Requirements.....             | 5 |
| Engineering Scheme and Design for Different Scenarios..... | 6 |

## Purpose of this Document

This document describes the engineering design and installation of 2MP License Plate Recognition Bullet IP Camera. It is intended for implementation and maintenance personnel of integrators and contractors. The personnel above are strongly recommended to read through this document before commencing the engineering design, device wiring, and installation.

## Product Introduction

Chart 2-1 Product introduction chart

| Model Number           | Features and Specification   | Remarks   |
|------------------------|--|---|
| i6-C721P-LZA 4.7-47mm  | 2MP Recognition of Vehicle License Plate Bullet IP Camera (4.7-47mm, WDR, Starlight, POE, H.265, White Light), | Telephoto version. Applicable scenarios: road sections, exit and entrance |
| i6-C721P-IRZA 4.7-47mm | 2MP Recognition of Vehicle License Plate Bullet IP Camera (4.7-47mm, WDR, Starlight, POE, H.265, Infrared),    |   |
| i6-C721P-LZA 2.8-12mm  | 2MP Recognition of Vehicle License Plate Bullet IP Camera (2.8-12mm, WDR, Starlight, POE, H.265, White Light), | Short-focus version. Applicable scenarios: exit and entrance              |
| i6-C721P-IRZA 2.8-12mm | 2MP Recognition of Vehicle License Plate Bullet IP Camera (2.8-12mm, WDR, Starlight, POE, H.265, Infrared),    |   |

## Site Survey

Before site survey, the general situation of the project should be studied, including: project background, scale, quality objectives, project starting and completion time. The engineering personnel should carefully study the bidding documents, project contracts, design schemes, drawings and other materials. After arriving at the site, a survey can be conducted according to the above project construction information to learn the actual situation of the site. And then determine the number and specific installation location of the device based on the customer's actual requirements.

### Site Survey Concerns

Telephoto camera is applied to road sections and exit and entrance scenarios. Short-focus camera is only applied to entrance scenarios.

For road section scenarios, it is recommended to front mount the camera at a straight road section. In the case of bend roads and steep slopes, please contact the product department to confirm the installation scheme.

For entrance scenarios, it is recommended to side mount the camera at a place where the width of the lane is between 3-4.5m and the distance from the camera to the capture point is more than 3 meters so that the vehicle can be straightened while going through the capture point. If the on-site environment is quite different from the ideal environment, please contact the product department to confirm the engineering scheme.

## Solution Guide to 2MP License Plate Recognition Bullet Camera

When applying the camera to a road section, the capable pole-mounting range at the road section must be confirmed, otherwise the capture rate would be affected. The distance from the pole to the capture point should be no less than 12m.

Avoid supplementary light and screen images being blocked by road signs, guide signs, trees and sentry boxes.


## Engineering Scheme

### Sketch of Installation Angle Requirements


#### Algorithm requirements:

- (1) The horizontal angle between the camera installation position and the center of the license plate should be no more than  $45^\circ$
- (2) The vertical angle between the camera and the license plate should be no more than  $30^\circ$
- (3) The horizontal tilt angle of the license plate should be no more than  $\pm 15^\circ$
- (4) The pixel size of the license plate should be between 90 to 300pix, and the most recommended recognition pixel size is about 130pix


Diagram 4-1 Sketches of Installation Angle Requirements



The horizontal angle  $\leftarrow$   
should be no more than  $45^\circ$



The vertical angle  $\leftarrow$   
should be no more than  $30^\circ$



The horizontal tilt angle  $\leftarrow$   
should be no more than  $\pm 15^\circ$



The pixel size of the license plate  
should be between 90 to 300pix


## Solution Guide to 2MP License Plate Recognition Bullet Camera

### Engineering Scheme and Design for Different Scenarios

**Chart 4-1** Recommended Engineering Scheme

| Model Number         | Road width W (m) | Camera Height H(m) | Distance to the capture point L(m) | Distance from the camera to the road curb S (m)   | Recommended Scheme | Recommended scenarios | Camera installation methods  |
|----------------------|------------------|--------------------|------------------------------------|---|--------------------|-----------------------|------------------------------|
| i6-C721P<br>4.7-47mm | $W \leq 4$       | 1.5-2              | 4-7                                | -0.3 (30cm from the road curb to the inward side) | H=1.5m<br>L=4m     | Exit and entrance     | Side mounting                |
|                      | $4 < W \leq 5$   | 2-2.5              | 5-8                                |   | H=2m<br>L=5m       |                       |                              |
|                      | $5 < W \leq 6$   | 2.5-3              | 6-12                               |   | H=2.5m<br>L=7m     |                       |                              |
|                      | $6 < W \leq 7$   | 3-6                | 12-26                              | 0-7   | H=6m<br>L=23m      | Road Section          | Front mounting/Side mounting |
| i6-C721P<br>2.8-12mm | $W \leq 4$       | 1.5-2              | 4-7                                | -0.3 (30cm from the road curb to the inward side) | H=1.5m<br>L=4m     | Exit and entrance     | Side mounting                |
|                      | $4 < W \leq 5$   | 2-2.5              | 5-8                                |   | H=2m<br>L=5m       |                       |                              |
|                      | $5 < W \leq 7$   | 2.5-3              | 7-12                               |   | H=2.5m<br>L=7m     |                       |                              |

**Diagram 4-2** Engineering reference for scenario with installation height of 1.5m-3m:



**Diagram 4-3** Engineering reference for scenario with installation height of 3m-6m:

